




Discover how
D-TEC trailers
can drive your
success.



Tank Trailer series



Whether transporting
biogas digestate,
manure, industrial
waste or other liquids,
a D-TEC is always the
smart choice.

Discover the benefits of a D-TEC Tank Trailer

Lightweight and stable

Thanks to its self-supporting tank design and short wheelbase, D-TEC offers both low tare weight and a low centre of gravity.

Reduced tire wear and ground damage

The unique forced steering system, lift-axle options, and trailing axle ensure maximum manoeuvrability while significantly reducing tyre wear and ground impact.

Fast loading and unloading

Optimized pumping systems, piping, and tank inclination – combined with various docking connections – make loading and unloading faster, cleaner, and more efficient than ever.

Tailored excellence

A wide range of smart options allows you to configure a trailer that fits your requirements – perfectly suited to your operation.

Flexible in use

Our pumping systems allow flushing during unloading, filling other tanks, or transferring wastewater or sludge to silos.

Maximum return, minimum cost


Every detail of a D-TEC trailer is engineered for maximum efficiency and the lowest Total Cost of Ownership. With D-TEC, you benefit from the lowest cost per kilometre and a high residual value – whether you're investing for five years or fifteen.



PO Box 110
4040 DC Kesteren
The Netherlands

Tel: +31 (0)488 740 030
info@d-tec.eu

www.d-tec.eu



Lift up your profit 

Multiliner
FV2006



Quickliner
FV2011



Reachliner
FV2023



Multiliner
SV2006



Quickliner
SV2011



Vacuumliner
SV-VAC




D-TEC Tank Trailer Series

+	++	+	6540	28,5–36m³	++	×	2006 / Lobe	++	+	++	++*	++	+	++*	++*	×	++*	++
++	++		6460	29,5–30,5m³	++	×	2011 / Lobe	+	++	+/-	×	++*	×	×	×	×	×	×
++	++	+	6360	29,5m³	++	×	2023 / Lobe	+	+	++*	++*	+	×	×	×	×	++*	×
		++	5610	28,5–35m³	×	+	2006 / Lobe	++	+	++*	++*	++	+	++*	×	++*	++*	++
	+	+	5450	30–31m³	×	+	2011 / Lobe	+	++	+/-	×	++*	×	×	×	×	×	×
+	+	+	6700	30m³	×	+	VAC / Vacuum	×	+/-	+	×	++	+	×	×	×	×	×

- ++ Excellent
+ Good
+/- Moderate
× Unsuitable
* Optional

<15 km	<100 km	>100 km																
			Weight from (30m³)	Volume	D-TEC steering system	Self-steering axle	Pump setup¹	Flushing lines	(Un)loading speed	Sealing of vessel	Trailer as pump station	(Un)loading via free fall	Electrical control box	Sampling system	Calibrated weighing	Container arm	Compact suction boom	Industrial waste & animal feed options


Options




Short catwalk



Long catwalk




Flushing lines




Filling dome




Andock on top




Andock at rear



Stainless steel toolbox




Baffle



D-TEC steering

¹Pump setup



Rotary lobe pump tanker



- Loading/unloading speed <6,5 min
- Low empty weight
- Requires a constant flow
- Handles material up to 60% dry matter
- Recirculation system – clean your tank from solids
- Easy unloading to higher ground level

Vacuum pump tanker



- Loading/unloading speed <20 min
- Higher empty weight (+800–1000kg)
- Suited for fluctuating material flow and larger pieces e.g. stones
- Pump is not exposed to the material flow
- Low in maintenance
- Suction with long transport hoses

Our D-TEC trailers stand out through their unique combination of:

- Low dead weight for maximum payload and efficiency
- User-friendliness thanks to smart, practical design
- Low maintenance costs through durable construction and simple systems
- High residual value that secures your long-term investment

